





YC-1320L

High-quality product
Seven sensors
Temperature uniformity
Ensuring safety of storage



Temp. Uniformity



Pulling down to 5°C



Temp. recovery after
door opened for 1 min

*Typical freezer data based on internal testing with freezer set point at 5°C and ambient temperature at 25°C.

Features



Temperature control system
Display temp. in 0.1°C increments



Double-pane glass door
Automatic electric heating function



Hydrocarbon refrigerant
Environment-friendly natural gas



CE certificate



Built-in data logger
Export up to 12 months of temperature data





Alarms system
Multiple alarm functions

Structure



● Dimensions



● Specification

2~8℃ Pharmacy Refrigerator		
Model	YC-1320L	
Capacity	1320L	
Internal Size (W*D*H) mm	1340×670×1515	
External Size (W*D*H) mm	1453*826*1998	
Package Size (W*D*H) mm	1588*991*2179	
NW/GW (kgs)	258/350	
Performance		
Temperature Range	2~8℃	
Ambient Temperature	16~32℃	
Cooling Performance	5℃	
Climate Class	N	
Controller	Microprocessor	
Display	7"HD IntelligentTouch Screen	
Refrigeration		
Compressor	1pc	
Cooling Method	Air Cooling	
Defrost Mode	Automatical	
Refrigerant	R290	
Insulation Thickness(mm)	D:55, L/R:55, B:55, U/D:65/80	
Construction		
External Material	PCM	
Inner Material	Stainless Steel	
Shelves	10	
Access Test Port	1pc. Ø 25 mm	
Casters	4+2	
Data Logging/ Interval /Recording Time	USB/Record every 5 minutes/100,000 data	
Interface	Remote Alarm Contact, RS485	
Backup Battery	Yes	
Alarms		
Temperature	High/Low Temperature, High Ambient Temperature, Condenser High Temperature Alarm	
Electrical	Power Failure, Low Battery, Sensor Error	
System	Data Communication Failure, Door Ajar,Data Logger Failure	
Electrical		
Power Supply(V/Hz)	110V/60Hz	220-240V;50/60Hz
Rated Current(A)	10.55A	5.59A